

GS Caltex India Private Limited

Global Premium Lubricants

GS COOLANT READY TO USE

Radiator Coolant

GS COOLANT READY TO USE is superior quality of ready to use type of engine coolant, which protects the radiator and engine parts. It is blended with very pure monoethylene glycol and selective rust and corrosion inhibitor to protect the metal parts in corrosive condition.

GS COOLANT READY TO USE is suitable in all climatic conditions and over wide temperature range. It operates and safeguards the engine against winter freezing, against high temperature operations and against corrosion.

GS COOLANT READY TO USE is premixed with deionised water. The premix ensures uniform mixing of coolant and it is easy to handle. It minimizes the risk of deposit formation because of poor water quality, the deposits that cause coolant circuit blockage and heat transfer properties resulting overheating of engine.

APPLICATIONS

Recommended for all type of passenger cars and light and heavy-duty vehicles. To get maximum performance, it is recommended to rinse the circuit before refilling if it contains another product.

BENEFITS

- Provides good heat distribution
- Minimum risk of overheating
- Minimize overheating of engine lubricant
- Neutralizes acid combustion gases which enter into cooling circuits
- Compatible with metal, hose and plastic parts

KEY PROPERTIES

Color	Density @ 20°C, kg/l	рН	Reserve alkalinity	Boiling Point, °C (50% solution)
Fluorescent Green	1.067	8.20	2.30	108

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected.

It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by GS Caltex Corporation.

(10/2012)

GS Caltex India Private Limited |