

# KIXX ATF SYNTHETIC

## AUTOMATIC TRANSMISSION FLUID

### DESCRIPTION

Kixx ATF Synthetic is a high performance, high quality multi-vehicle fluid for automatic transmissions.

It is a specially formulated fluid designed to meet the requirements of a wide range of Automatic Transmission Specifications. In addition it meets the requirements of European OEM specifications.

Kixx ATF Synthetic is based on VHVI Synthetic technology.

### PERFORMANCE STANDARDS

- API JASO M315 Type 1A
- Toyota Type T,T-II,T-III,T-IV and D-2
- Hyundai, Kia SP-III
- Mitsubishi SP-II, SP-III
- GM DEXRON III
- MERCON
- Nissan Matic Fluid C,D,J
- Subaru ATF
- Isuzu BESCO ATF-II, III
- Suzuki ATF Oil, ATF Oil Special
- Mazda ATF D-II, ATF M-III
- 4, 5 Speed European (BMW, MB, VW)
- ZF Commercial ATs (TE-ML 14A)
- Voith Commercial ATs (55.6335)
- MAN Commercial ATs (MAN339 Type Z-1)

### BENEFITS

- Anti shudder protection.
- Oxidation and thermal stability
- Provides high foam stability
- Provides good start operation in cold climates by excellent low-temperature fluidity
- Provides more stable friction property
- More advanced than conventional transmission fluids

### KEY PROPERTIES

<b>Kinematic Viscosity @ 40°C (mm<sup>2</sup>/s)</b>	37
<b>Kinematic Viscosity @100°C (mm<sup>2</sup>/s)</b>	7.6
<b>Brookfield Viscosity @-20°C</b>	1300
<b>Brookfield Viscosity @-40°C</b>	13800
<b>Flash Point (°C)</b>	225
<b>Pour Point (°C, COC)</b>	-42

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by GS Caltex Corporation