

KIXX MP-3 GREASE

NLGI 3

MULTIPURPOSE GREASE

DESCRIPTION

Multipurpose grease containing highly refined mineral base oils, lithium thickener and rust and oxidation inhibitors. Suitable for automotive and industrial applications.

APPLICATIONS

- Plain and rolling element bearings.
- Automotive and General plant lubrication.
- Construction equipment bearings.
- Earthmoving, quarrying and mining.
- Agricultural equipment.

Usable temperature range: -20 to +130°C. Maximum temperature for short term exposure: +155°C.

PERFORMANCE STANDARDS

• NLGI 3.

BENEFITS

- Saves on maintenance.
 - o Protection against component wear under moderate load conditions.
 - o Rust and corrosion inhibitors protect metal surfaces.
- Long service life.
 - o Excellent oxidation resistance ensures enhanced grease service life.
- Minimizes inventory costs.
 - o Multipurpose capability allows use in a wide range of industrial and automotive applications reducing the number of different greases required and eliminating product misapplication.

KEY PROPERTIES

NLGI Grade	3
Thickener	Lithium Soap
Penetration, Worked @ 25°C	235
Dropping Point, °C	196
Copper Corrosion @ 100°C, 24hrs	1b max
Oxidation Stability, kgf/cm2 @ 99°C,100hrs	0.4

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by GS Cattex Corporation.