

KIXX DYNAMIC DIESEL

API CF-4, SAE 15W-40

DESCRIPTION

Kixx Dynamic Diesel CF-4 15W-40 is high performance, multigrade diesel engine oil specially designed to lubricate a wide range of diesel and gasoline engines requiring API CF-4 performance lubricants.

APPLICATION

- Recommended for use in turbo charged trucks and tractors where API CF-4 performance is recommended by the OEM.
- It is also recommended to be used in LCV/MCV, Mini-vans and Gensets.

PERFORMANCE STANDARDS

- API CF-4

BENEFITS

- Excellent protection against oxidation which helps in increased oil service life
- Superior performance against sludge formation which protects engine for longer period
- Ensures superior protection against thickening of oil and carbon deposit build up in critical components
- Lower maintenance cost and reduced downtime enables improved profitability

KEY PROPERTIES

SAE GRADES	15W 40
Kinematic Viscosity @ 100°C (mm ² /s)	14.91
Kinematic Viscosity @ 40°C (mm ² /s)	111.7
Viscosity Index	132
Pour Point (°C)	-24
Flash Point (°C, COC)	240
TBN, mg KOH/g (ASTM 2896)	10

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by GS Caltex Corporation