

## KIXX GEARTEC GL-5

SAE 75W-90 / 80W-90 / 85W-140

### MULTIGREAD AUTOMOTIVE GEAR OIL

#### DESCRIPTION

High-performance, multipurpose, thermally stable, EP automotive gear lubricant.

#### APPLICATIONS

- Recommended for automotive hypoid gear applications requiring lubricants meeting API Service GL-5 or where EP, multi-purpose or hypoid type gear oils are specified.
- Recommended where loading is severe and maximum gear protection is required. “Clean gear” technology makes it particularly suitable where gear oil temperatures are high.
- Not recommended for manual transmissions and transaxles where the manufacturer specifies API GL-4(mild-EP) lubricants, or where the manufacturer advises against the use of API GL-5 (multipurpose, hypoid) lubricants.

#### PERFORMANCE STANDARDS

- API GL-5

#### BENEFITS

- Provides long equipment life by resisting gear wear and scuffing, Reduced maintenance costs.
- Maximizes equipment availability by avoiding premature failure or need for overhaul due to deposit-induced seal wear and leakage.
- Provides long oil service life by resisting oxidation and oil thickening.
- Provides protection against corrosion of ferrous and non-ferrous components.

#### KEY PROPERTIES

SAE Grades	75W-90	80W-90	85W-140
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	85.7	135.6	343.9
Kinematic Viscosity @100°C (mm <sup>2</sup> /s)	14.56	14.1	25.5
Viscosity Index	178	109	97
Pour Point (°C)	-43	-27	-15
Flash Point (°C, COC)	225	236	248