

KIXX HDX EURO API CJ-4, SAE 10W-30/15W-40

ADVANCE TECHNOLOGY LOW SAPS DIESEL ENGINE OIL

API CJ-4 SAE 15W-40/ 10W-30

DESCRIPTION

Premium performance, multi-grade, heavy-duty diesel engine oil specifically designed for new low emission engines with ULSD (Ultra Low Sulfur Diesel

APPLICATIONS

- Kixx HDX Euro is a mixed fleets motor oil recommended for all naturally aspirated and turbocharged four-stroke diesel engines and four-stroke gasoline engines in which the API CJ-4 grade is recommended
- Formulated for superior performance with ULSD but also with both normal and low sulfur diesel fuels
- Off-highway and construction applications which require an API CJ-4 Service Category

PERFORMANCE STANDARDS

- API CJ-4;CI-4 PLUS, CI-4/SN
- VOLVO VDS 4
- MACK EO-O PREMIUM PLUS
- RLD -3
- CUMMINS CES 20081
- CATERPILLAR CAT ECF-3
- DETROIT DIESEL DDC 93 K218

- FORD WSS-M2C171-F1
- ACEA E9-16 (2016)
- MB 228.31
- MTU TYPE -2.1
- MAN 3575
- Deutz DQC III-10 LA

BENEFITS

- Extends Diesel Particulate Filter (DPF) life for less frequent downtime and cleaning, thus decreasing maintenance costs.
- Backwards compatible with all previous API Oil Service Categories and engine models. Single oil for all services, in four stroke gasoline and all naturally aspirated turbocharged and modern electronically controlled/low emission diesel engines.
- One oil that allows users with a wide mix of engine brands to enjoy simplified inventory and dispensing systems that help save money, space, handling time, and avoid product misapplication.

KEY PROPERTIES

SAE GRADES	15W-4	40 10W-30
Viscosity @ 40°C (mm²/s)	121.2	2 76.48
Viscosity @100°C (mm²/s)	16.0	11.4
Viscosity Index	140	141
Pour Point (°C)	-39	-39
Flash Point (°C)	232	230
TBN, mg KOH/g, (ASTM 2896)	8.3	8.1

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they A 50-50 joint venture of GS Energy. South Korea & Chevron LISA