

KIXX ULTRA 4T XP

API SL, JASO MA2, SAE 10W-30

DESCRIPTION

Kixx Ultra 4T XP is a high-quality engine oil designed to meet requirements of four-stroke motorcycle engines where API SL performance is required. Meets friction tests stipulated in JASO MA2

Kixx Ultra 4T XP is a engine oil with advanced additive technology to deliver excellent performance in modern vehicles meeting BS VI norms.

APPLICATION

- Air and liquid-cooled four-stroke motorcycle engines
- Particularly suitable for Japanese high-performance motorcycle engines.
- Motorcycles with exhaust catalytic converters
- Suitable for all motorcycle engines, both carburetor and fuel injected where API SN or below and JASO MA and MA2 are recommended.

PERFORMANCE STANDARDS

- API SL
- JASO MA2

BENEFITS

- Lower deposits indicating good oxidation stability and cleaner engine parts at high temperatures.
- Better oxidation resistance, lower oxidative oil thickening, Higher oil life.
- Good wear control – Protection of valve train & gear interface
- Trouble free operations.

KEY PROPERTIES

SAE GRADES	10W-30
Kinematic Viscosity @ 100°C (mm ² /s)	10.3
Kinematic Viscosity @ 40°C (mm ² /s)	70.3
Viscosity Index	131
Pour Point (°C)	-30
Flash Point (°C, COC)	232
TBN, mg KOH/g (ASTM 2896)	6.0

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by GS Caltex Corporation